

DRAWING NUMBER
900032

ISSUE
A

THE INFORMATION CONTAINED IN THIS DRAWING IS PROPRIETARY AND MUST NOT BE COPIED OR DISCLOSED TO THIRD PARTIES WITHOUT PRIOR WRITTEN CONSENT FROM THE OWNER

FRONT GLASS DOOR

5/8"-11 LIFTING EYE BOLT

NEOPRENE WASHER

ENCLOSURE

REAR LOWER ACCESS COVER

FRONT LOWER ACCESS COVER

FRONT VIEW

REAR VIEW

TOLERANCES EXCEPT WHERE OTHERWISE STATED:

HOLE DIAMETER ± 0.08


X ± 0.50

X.X ± 0.25

X.XX ± 0.13

ANGLE $\pm 0.5^\circ$

ALL DIMENSIONS IN MM (INCHES)

PROJECTION 

NEXT ASSEMBLY

MATERIAL
Material <not specified>

FINISH
-

DRAWN
NAK

DATE
4/10/2018

APPROVED
STC

SIZE
A3

DRAWING NUMBER
900032

SCALE/PROJECT
1:15 V12-MP

TITLE
FIELD ASSEMBLY DETAIL - DOUBLE

PART NUMBER
900032

DRAWING NUMBER
900032

ISSUE
A

STRATACACHE

1 OF 5

REFERENCE 3D GEOMETRY FOR MISSING DIMENSIONS

REMOVE ALL BURRS AND SHARP EDGES

CAD model file: 900032 (Default)

DRAWING NUMBER
ISSUE

900032
A

STEP 2

- USE A SUITABLE LIFTING DEVICE TO LOWER THE PACKAGED DISPLAY TO GROUND LEVEL... ESTIMATED PACKAGED WEIGHT = 835LBS.
- WITH THE UNIT SAFELY ON THE GROUND, REMOVE ALL PACKAGING MATERIALS.
- USE THE KEY PROVIDED TO UNLOCK AND SLIDE APART THE LOWER ACCESS COVERS (FRONT AND REAR).
- REMOVE BOLTS CONNECTING THE DISPLAY TO THE PALLET.
- KEEP THE LOWER ACCESS COVERS (FRONT AND REAR) ASIDE PRIOR TO MOVING THE DISPLAY UNIT.
- USE THE FACTORY INSTALLED EYE BOLTS TO LIFT THE ENCLOSURE OFF THE PALLET AND ON TO THE PREPARED CONCRETE FOUNDATION... LEVEL THE SYSTEM AS REQUIRED AND SECURE TO THE ANCHORS WITH FLAT WASHERS (OR PLATE WASHERS), LOCK WASHERS, AND HEX NUTS.
- ONCE DISPLAY UNIT IS SECURED TO THE FOUNDATION REPLACE AND SECURE LOWER ACCESS COVERS

STEP 2.6

STEP 2.3
STEP 2.5

STEP 2.7

DETAIL B
SCALE 1 : 3
(4 PLCS)

TOLERANCES EXCEPT WHERE OTHERWISE STATED:

HOLE DIAMETER ± 0.08

X ± 0.50

X.X ± 0.25

X.XX ± 0.13

ANGLE $\pm 0.5^\circ$

NEXT ASSEMBLY

MATERIAL
Material <not specified>

FINISH

ALL DIMENSIONS IN MM (INCHES)

PROJECTION

DRAWN NAK	DATE 4/10/2018	SIZE A3
APPROVED STC	DATE 4/10/2018	SCALE 1:12

STRATACACHE

TITLE
FIELD ASSEMBLY DETAIL - DOUBLE

PART NUMBER
900032

DRAWING NUMBER
900032

PROJECT
V12-MP

SHEET 3 OF 5

ISSUE
A

[REFERENCE 3D GEOMETRY FOR MISSING DIMENSIONS]
REMOVE ALL BURRS AND SHARP EDGES

CAD model file: 900032 (Default)

DRAWING NUMBER
900032

ISSUE
A

THE INFORMATION CONTAINED IN THIS DRAWING IS PROPRIETARY AND MUST NOT BE COPIED OR DISCLOSED TO THIRD PARTIES WITHOUT PRIOR WRITTEN CONSENT FROM THE OWNER

STEP 1

- PREPARE MOUNTING SURFACE (FOOTING OR ADAPTER PLATE) AS REQUIRED IN ACCORDANCE WITH ENGINEER APPROVED SITE DRAWING. CONSTRUCTION MUST COMPLY WITH LOCAL BUILDING CODES, DESIGN LOADS AND ENVIRONMENTAL CONDITIONS.
- THE MOUNTING SURFACE MUST INCLUDE 4X THREADED ANCHORS FOR CONNECTING THE SIGN STRUCTURE ACCORDING TO THE BOLTING PATTERN AS SHOWN. THREADED ROD SIZE AND EMBEDMENT TO BE AS SPECIFIED BY THE SITE ENGINEER.
- ADJUST LOWER HARDWARE AS NEEDED TO ACHIEVE A LEVEL MOUNTING CONDITION.

PLAN VIEW (ANCHOR DETAIL)

1'-10 15/16"

8"

8"

1'-5/8"

ANCHOR PLATE

PREFERRED 8" X 8" ANCHOR PATTERN IS SUBJECT TO APPROVAL BY THE SITE ENGINEER

(4) Ø 3/4" THREADED RODS W/EMBEDMENT PER ENGINEER APPROVED SITE DRAWING

RIGID CABLE CONDUIT

ENCLOSURE STRUCTURAL FRAME

STEP 1.2

STEP 1.1

CONCRETE FOOTING IN ACCORDANCE W/ENGINEER APPROVED SITE DRAWING

5 1/16"

4 1/16"

DETAIL A SCALE 1 : 4

STEP 1.3

TOLERANCES EXCEPT WHERE OTHERWISE STATED:

HOLE DIAMETER ±0.08
X ±0.50
X-X ±0.25
X-X ±0.13
ANGLE ±0.5°

ALL DIMENSIONS IN MM (INCHES)

PROJECTION

NEXT ASSEMBLY

MATERIAL	Material <not specified>
FINISH	-

DRAWN NAK DATE 4/10/2018 SIZE A3

APPROVED DATE 4/10/2018 SCALE PROJECT 1:8

DRAWING NUMBER 900032

ISSUE A

SHEET 2 OF 5

STRATACACHE

TITLE FIELD ASSEMBLY DETAIL - DOUBLE

PART NUMBER 900032

DRAWING NUMBER 900032

SCALE PROJECT 1:8

V12-MP

REFERENCE 3D GEOMETRY FOR MISSING DIMENSIONS

REMOVE ALL BURRS AND SHARP EDGES

CAD model file: 900032 (Default)

DRAWING NUMBER
900032

ISSUE
A

STEP 3

- REMOVE LIFTING EYE BOLTS AND ITS HARDWARE AND PLUG HOLES W/ SEALING WASHERS AND BOLTS SUPPLIED IN KIT.
- ENSURE THAT THE AC MAIN SUPPLY CIRCUIT BREAKER IS OFF.
- USE PHILIPS SCREWDRIVER TO REMOVE WEATHERPROOF COVER TO ACCESS AC PORTION OF CABLE BOX.
- FIELD TECHNICIAN TO PROVIDE LIQUID TIGHT FITTING TO ATTACH TO 1" DIAMETER HOLE. ONCE ATTACHED, FEED POWER CABLES FROM THE CONDUIT THROUGH FITTING.
- CONNECT INPUT POWER TO THE SYSTEM IN ACCORDANCE WITH WIRING SCHEMATICS (DETAIL D)
- SCREW BACK ON WEATHERPROOF COVER. ENSURE SWITCH IS TURNED ON
- CONNECT EARTH GROUND LINE TO M5 GROUND STUD WITH PROVIDED HARDWARE
- ASSEMBLE CUSTOMER'S CAT6 ETHERNET CABLES WITH THE LIQUID TIGHT FEED THRU CONNECTOR SUPPLIED IN KIT AND CONNECT TO THE DISPLAY UNIT.

DETAIL C
SCALE 1 : 5

DETAIL D
SCALE 1 : 2

REFERENCE 3D GEOMETRY FOR MISSING DIMENSIONS

REMOVE ALL BURRS AND SHARP EDGES

STRATACACHE

TOLERANCES EXCEPT WHERE OTHERWISE STATED:		NEXT ASSEMBLY		<p>TITLE FIELD ASSEMBLY DETAIL - DOUBLE</p> <p>PART NUMBER 900032</p>	
HOLE DIAMETER ±0.08 X +0.50 X +0.25 X-X +0.13 ANGLE ±0.5°		MATERIAL Material <not specified> FINISH -			
ALL DIMENSIONS IN MM (INCHES)		DRAWN NAK	DATE 4/10/2018	SIZE A3	DRAWING NUMBER 900032
PROJECTION		APPROVED STC	DATE 4/10/2018	SCALE 1:20	PROJECT V12-MP
					ISSUE A SHEET 4 OF 5

CAD model file: 900032 (Details)

[illegible]